

Appendix B 25008152

1. 240 Meters

Steel Pipe Longitudinally Welded with ends beveled angle 30 degrees (both sides).

56" Outside Dia. x 0.5" wall thickness.

Grade and specification: API 5L grade B PSL1 or AWWA-B.

Each length: 11.2-11.80 Mtr.

Outside Coating: Bare.

Inside Coating: Bare

Pipe end protection: with hook-hold plastic/Metal caps.

Mill Test Certificate to EN 10204/3.1 according to API Standards 5LX including chemical and physical properties.

Manufacturer: European Only. Eur1 certificate will be required

2. 276 Meters

Steel Pipe Longitudinally welded with ends beveled angle 30 degrees (both sides).

42" Outside Dia. x 0.5" wall thickness.

Grade and specification: API-5L-X60 PSL2

Each length: 12 Mtr.

Inside Coating: Bare

Outside Coating: HDPE Coating according to Din 30670, 4.0 mm thickness

Pipe end protection: with hook-hold plastic/Metal caps.

Testing and Acceptance:

- Mill test certificate to EN 10204/3.2 to API Standards 5LX including chemical and physical properties.
- 100% ultrasonic, X-ray and hydrostatic test reports.
- Third Part inspection made by LLOYDS or Bureau Veritas.

Manufacturer: European Only. Eur1 certificate will be required

All Pipes must be manufactured by one or more of the manufacturers included in the list below:

- Salzgitter Mannesmann Line Pipe GmbH
- Tenaris S.A.
- Interpipe Limited
- Liberty Galaty
- Vallourec